

Utilities and Transportation Commission

Standard Inspection Report for Intrastate Hazardous Liquid Systems

Procedures and Plan Review

S – Satisfactory U – Unsatisfactory N/A – Not Applicable N/C – Not Checked
 If an item is marked U, N/A, or N/C, an explanation must be included in this report.

A completed **Standard Inspection Checklist, Cover Letter and Field Report** are to be submitted to the Senior Engineer within **30 days** from completion of the inspection.

Inspection Report			
Inspection ID/Docket #	6772		
Inspector Name & Submit Date	Scott Anderson, submitted 5/23/2016		
Chief Engineer Name & Review Date	Joe Subsits 5/24/16		
Operator Information			
Name of Operator:	Targa Sound Terminal	OPID #:	38921
Name of Unit(s):	Headquarters		
Records Location:	Tacoma, WA		
Date(s) of Last (unit) Inspection:	Standard Insp. Lex Vinsel 2/2015	Inspection Date(s):	5/16-5/17/2016

<p>Inspection Summary: This inspection was a review of the O&M Manual of Targa Sound Terminal, LLC., there were no probable violations. Any changes or additions that needed to be added to the manual were done onsite. The revised O&M manual will be sent around June.</p> <p>Located in the Hylebos waterway in Tacoma, Targa provides bulk liquid storage and supplies fuels, lubricants, and other products and services to industry. The pipeline was mostly installed using HDD and for 90% of length is more than 50 feet deep. There are two CP test points, 1 booster pump station at Olympics' DP and 1 breakout tank necessary to relieve surges.</p>

HQ Address:		System/Unit Name & Address:	
Targa Resources 1000 Louisiana, Ste. 4300 Houston, TX 77002		Targa Sound Terminal, LLC 2628 Marine View Dr. Tacoma, WA 98422	
Co. Official:	Vincent DiCosimo	Phone No.:	253-272-9348
Phone No.:	713-584-1235	Fax No.:	
Fax No.:		Emergency Phone No.:	253-272-9348
Emergency Phone No.:			
Persons Interviewed	Title	Phone No.	
Matthew Kolata	EH&S Specialist	(253) 579-1947	
Tom Metcalf	Pipeline Supervisor	(253) 272-9348	

CONVERSION TO SERVICE			S	U	N/A	N/C
1.	195.5(a-c)	Has a written procedure been developed addressing all applicable requirements and followed?	X			

REGULATED RURAL GATHERING LINES			S	U	N/A	N/C
2.	195.11	Operator has identified pipelines that are Regulated Rural Gathering Lines that meet all of the following criteria: (1) nominal diameter from 6 5/8 inches to 8 5/8 inches; (2) located in or within one-quarter mile of a USA (3) operates at an MOP established under §195.406 that is: (i) greater than 20% SMYS; or (ii) if the stress level is unknown, or not steel; > 125 psig.			X	
3.	195.11(b)	Operator has prepared written procedures to carry out the requirements of 195.11 . <ul style="list-style-type: none"> • Subpart B Reporting • Corrosion Control • Damage Prevention • Public Awareness • Establish MAOP • Line Markers • Operator Qualification 			X	
4.	195.11(c)	If a new USA is identified after July 3, 2008, the operator must implement the requirements in paragraphs (b)(2 - 8), and (b)(11) for affected pipelines within 6 months of identification. For steel pipelines, comply with the deadlines in paragraphs (b)(9 & 10).			X	
5.	195.11(d)	Operator must maintain : (1) Segment identification records required in paragraph (b)(1) of this section and the records required to comply with (b)(10) of this section, for the life of the pipe. (2) records necessary to demonstrate compliance (b)(2 – 9 & 11) of this section according to the record retention requirements of the referenced section or subpart.			X	

Comments:

1-5. Targa Sound Terminal, LLC. does not have any regulated gathering lines.

LOW-STRESS PIPELINES IN RURAL AREAS			S	U	N/A	N/C
6.	195.12(a)	Operator has identified pipelines that are Regulated Low-stress Pipelines in Rural Areas that meet all of the following criteria: (except for those already covered by 49 CFR 195) (1) nominal diameter of 8 5/8 inches or more; (2) located in or within one-half mile of a USA (3) operates at an MOP established under §195.406 that is: (i) greater than 20% SMYS; or (ii) if the stress level is unknown, or not steel; > 125 psig.			X	
7.	195.12(b)	Operator has prepared written procedures to carry out the requirements of 195.12. <ul style="list-style-type: none"> Subpart B Reporting Establish Integrity Management Plan All Part 195 Safety Requirements 			X	
8.	195.12(c)(1)	Operator may notify PHMSA of economic burden.			X	
9.	195.12(d)	If, after July 3, 2008, a new USA is identified, the operator must implement the requirements in paragraphs (b)(2)(i) for affected pipelines within 12 months of identification.			X	
10.	195.12(d)	Operator must maintain: (1) Segment identification records required in paragraph (b)(1) for the life of the pipeline. (2) Records necessary to demonstrate compliance (b)(2 - 4) according to the record retention requirements of the referenced section or subpart.			X	

Comments:

#6-10. Targa Sound Terminal, LLC. does not have any low-stress pipelines in rural areas.

SUBPART B - REPORTING PROCEDURES			S	U	N/A	N/C
11.	195.402(a) 195.402(c)(2)	Complete and submit DOT Form PHMSA F 7000-1.1 for each type of hazardous liquid pipeline facility operated at the end of the previous year for each commodity, and each state a pipeline traverses by June 15 of each calendar year. (NOTE: August 15, 2011 for the year 2010). (Amdt. 195-95, 75 FR 72877, November 26, 2010, eff. 1/1/2011). .49 ***O&M SEC 03 PAGE 12/SEC 05 PAGE 2***	X			
12.		Accident report criteria, as detailed under 195.50. A release that results in, 5 gallons or more, death or personal injury necessitating hospitalization , an explosion or fire not intentionally set by the operator , or total estimated property damage including clean-up and product lost equaling \$50,000 or more. (Note: A release of less than 5 gals may still require reporting. See 195.50(b) and 195.52(a)(4) for additional requirements and exemptions for maintenance work under 5 BBLS). .50 ***O&M SEC 03 PAGE 6***	X			
13.		Immediate notice to NRC (800) 424-8802 , or electronically at http://www.nrc.uscg.mil , of certain events, and additional report if significant new information becomes available. Operator must have a written procedure for calculating an initial estimate of the amount of product released in an accident. (Amdt. 195-95, 75 FR 72878, November 26, 2010, eff. 1/1/2011). .52 ***O&M SEC 03 PAGE 7, 9***	X			
14.		Accident Report - file as soon as practicable, but no later than 30 days after discovery. Submittal must be electronically to http://pipelineonlinereporting.phmsa.dot.gov (Amdt. 195-95, 75 FR 72878, November 26, 2010). .54(A) ***O&M SEC 03 PAGE 7***	X			
15.		Supplemental report - required within 30 days of information change/addition .54(b)	X			

SUBPART B - REPORTING PROCEDURES			S	U	N/A	N/C
		O&M SEC 03 PAGE 7				
16.		Safety-related conditions (SRC) - criteria .55 ***O&M SEC 03 PAGE 4***	X			
17.		SRC Report is required to be filed within five (5) working days of the determination and within ten (10) working days after discovery .56(a) ***O&M SEC 03 PAGE 4***	X			
18.		SCR Report requirements, including corrective actions (taken and planned) .56(b) ***O&M SEC 03 PAGE 5***	X			
19.	195.402(a) 195.402(c)(2)	Reports (except SRCR and offshore pipeline condition reports) must be submitted electronically to PHMSA at http://portal.phmsa.dot.gov/pipeline unless an alternative reporting method is authorized IAW with paragraph (d) of this section. (Amdt. 195-95, 75 FR 72878, Nov. 26, 2010, eff. 1/1/2011). ***O&M SEC 03 PAGE 7***	X			
20.		Each operator must obtain an OPID, validate its OPIDs, and notify PHMSA of certain events at http://portal.phmsa.dot.gov/pipeline (Amdt. 195-95, 75 FR 72878, Nov.26, 2010, eff. 1/1/2011). .64(a-d) ***TARGA OPID 38921***	X			
WAC 480-75 REPORTING PROCEDURES			S	U	N/A	N/C
21.	480-75-610	Reporting of proposed pipeline construction 45 days prior to construction ***O&M SEC 05.2 PAGE 1***	X			
22.	480-75-620	Providing notice of hydrotest to change MOP ***ENG. & CONST. MANUAL PAGE 41***	X			
23.	480-75-630	Telephonic Reports to UTC Pipeline Safety Incident Notification 1-888-321-9144 (Within 2 hours of discovery) for events which results in; a) A fatality; (b) Personal injury requiring hospitalization; (c) Fire or explosion not intentionally set by the pipeline company; (d) Spills of five gallons or more of product from the pipeline; (e) Damage to the property of the pipeline company and others of a combined total cost exceeding twenty-five thousand dollars (automobile collisions and other equipment accidents not involving hazardous liquid or hazardous-liquid-handling equipment need not be reported under this rule); (f) A significant occurrence in the judgment of the pipeline company, even though it does not meet the criteria of (a) through (e) of this subsection; (g) The news media reports the occurrence, even though it does not meet the criteria of (a) through (f) of this subsection. ***O&M SEC 03 PAGE 10***	X			
24.	480-75-630(2)	Written reports to the commission within 30 calendar days of the incident. The report must include the following: a) Name(s) and address(es) of any person or persons injured or killed or whose property was damaged; (b) The extent of injuries and damage; (c) A description of the incident including date, time, and place; (d) A description and maximum operating pressure of the pipeline implicated in the incident and the system operating pressure at the time of the incident; (e) The date and time the pipeline returns to safe operations; and (f) The date, time, and type of any temporary or permanent repair. ***O&M SEC 03 PAGE 10***	X			
25.	480-75-630(3)	Notification within 24 hours of emergency situations including emergency shutdowns, material defects or physical damage that impairs serviceability? ***O&M SEC 03 PAGE 11***	X			
26.	480-75-630(4)	Filing Reports of Damage to Hazardous Liquid Pipeline Facilities to the commission. (eff. 4/1/2013) (Via the commission's Virtual DIRT system or on-line damage reporting form)				
27.	480-75-630(4)(a)	Does the operator report to the commission the requirements set forth in RCW 19.122.053(3) (a) through (n) ***O&M SEC 03 PAGE 11***	X			
28.	480-75-630(4)(b)	Does the operator report the name, address, and phone number of the person or entity that the company has reason to believe may have caused damage due to excavations conducted without facility locates first being completed? ***O&M SEC 03 PAGE 11***	X			
29.	480-75-630(4)(c)	Does the operator retain all damage and damage claim records it creates related to damage events reported under 93-200(7)(b), including photographs and documentation supporting the conclusion that a facilities locate was not completed? Note: Records maintained for two years and made available to the commission upon request. ***O&M SEC 03 PAGE 11***	X			
30.	480-75-630(5)	Does the operator provide the following information to excavators who damage				

SUBPART B - REPORTING PROCEDURES			S	U	N/A	N/C
		hazardous liquid pipeline facilities? ***O&M SEC 03 PAGE 16***				
31.	480-75-630(5)(a)	<ul style="list-style-type: none"> Notification requirements for excavators under RCW 19.122.050(1) ***O&M SEC 03 PAGE 16*** 	X			
32.	480-75-630(5)(b)	<ul style="list-style-type: none"> A description of the excavator's responsibilities for reporting damages under RCW 19.122.053; and ***O&M SEC 03 PAGE 16*** 	X			
33.	480-75-630(5)(c)	<ul style="list-style-type: none"> Information concerning the safety committee referenced under RCW 19.122.130, including committee contact information, and the process for filing a complaint with the safety committee. ***O&M SEC 03 PAGE 16*** 	X			
34.	480-75-630(6)	<p>Reports to the commission only when the operator or its contractor observes or becomes aware of the following activities...</p> <ul style="list-style-type: none"> An excavator digs within thirty-five feet of a transmission pipeline, as defined by RCW 19.122.020(26) without first obtaining a facilities locate; (630(6)(a) A person intentionally damages or removes marks indicating the location or presence of hazardous liquid pipeline facilities. 630(6)(b) ***O&M SEC 03 PAGE 16*** 	X			

Comments:

SUBPART C – INTERNAL DESIGN PRESSURE PROCEDURES			S	U	N/A	N/C
35.	195.402(c) 195.422	Internal design pressure for pipe in a pipeline is determined in accordance with the requirements of this section and the formula: $P = (2 St/D) \times E \times F$. .106 ***SEC 16 PAGE 1/DETERMINATION OF MOP WORKSHEET***	X			

SUBPART C - PASSAGE OF INTERNAL INSPECTION DEVICE PROCEDURES			S	U	N/A	N/C
36.	195.402(c) 195.422	Each new pipeline or each section of a pipeline which pipe or components has been replaced must be designed and constructed to accommodate the passage of instrumented internal inspection devices that are applicable to this section .120(a) ***O&M SEC 22 PAGE 1/E&C MANUAL PAGE 7***	X			

Comments:

SUBPART D – WELDING, NDT, and REPAIR /REMOVAL PROCEDURES			S	U	N/A	N/C
Compliance with welding requirements for pipe replaced or repaired in the course of pipeline maintenance is required by §195.422 and §195.200.						
37.	195.402(c) 195.422	Welding must be performed by qualified welders using qualified welding procedures. .214(a) ***E&C MANUAL PAGE 14/GENERAL WELDING PROCEDURES***	X			
38.		Are welding procedures qualified in accordance with Sec. 5 of API 1104 or Section IX of ASME Boiler & Pressure Code? ***E&C MANUAL PAGE 14/GENERAL WELDING PROCEDURES ***	X			
39.		Welding procedures must be qualified by destructive testing. ***E&C MANUAL PAGE 14/GENERAL WELDING PROCEDURES***	X			

SUBPART D – WELDING, NDT, and REPAIR /REMOVAL PROCEDURES			S	U	N/A	N/C
40.		Each welding procedure must be recorded in detail including results of qualifying tests. .214(b) ***E&C MANUAL PAGE 14/GENERAL WELDING PROCEDURES***	X			
41.		Welders must be qualified in accordance with Section 6 of API Standard 1104 (20th edition 2007, including errata 2008) or Section IX of the ASME Boiler and Pressure Vessel Code (2007 edition, July 1, 2007) , except that a welder qualified under an earlier edition than currently listed in 195.3 may weld, but may not re-qualify under that earlier edition. (Amdt 195-94 Pub. 8/11/10 eff. 10/01/10). .222(a) ***E&C MANUAL PAGE 14/GENERAL WELDING PROCEDURES***	X			
42.		Welders may not weld with a particular welding process unless, within the preceding 6 calendar months, the welder has -- (1) Engaged in welding with that process; and (2) Had one weld tested and found acceptable under Section 9 of API 1104. .222(b) ***E&C MANUAL PAGE 14/GENERAL WELDING PROCEDURES***	X			
43.		Arc burns must be repaired. .226(a) ***E&C MANUAL GENERAL WELDING PROCEDURES ARC BURN REPAIR***	X			
44.	195.402(c) 195.422	Do arc burn repair procedures require verification of the removal of the metallurgical notch by nondestructive testing? (Ammonium Persulfate). Pipe must be removed for non-repairable notches. .226(b) ***E&C MANUAL GENERAL WELDING PROCEDURES ARC BURN REPAIR***	X			
45.		The ground wire may not be welded to the pipe/fitting being welded. .226(c) ***E&C MANUAL GENERAL WELDING PROCEDURES ARC BURN REPAIR***	X			
Nondestructive Testing Procedures						
46.		Do procedures require welds to be nondestructively tested to ensure their acceptability according to API 1104 and as per 195.228(b) and per the requirements of 195.234 in regard to the number of welds to be tested? ***E&C MANUAL GENERAL WELDING PROCEDURES INSPECTION AND TESTING OF WELDS***	X			
47.		Nondestructive testing of welds must be performed: .234(b)				
48.	195.402(c) 195.422	1. In accordance with written procedures for NDT ***E&C MANUAL GENERAL WELDING PROCEDURES NON-DESTRUCTIVE TESTING***	X			
49.		2. By qualified personnel ***E&C MANUAL GENERAL WELDING PROCEDURES NON-DESTRUCTIVE TESTING***	X			
50.		3. By a process that will indicate any defects that may affect the integrity of the weld ***E&C MANUAL GENERAL WELDING PROCEDURES NON-DESTRUCTIVE TESTING***	X			
51.		Records of the total number of girth welds and the number nondestructively tested, including the number rejected and the disposition of each rejected weld, must be maintained. .266 ***E&C MANUAL GENERAL WELDING PROCEDURES NON-DESTRUCTIVE TESTING***	X			
Repair or Removal of Weld Defect Procedures						
52.	195.402(c) 195.422	Welds that are unacceptable must be removed and/or repaired. See .228 and .230 for exceptions. .230 ***E&C MANUAL GENERAL WELDING PROCEDURES NON-DESTRUCTIVE TESTING***	X			

Comments:

SUBPART E - PRESSURE TESTING PROCEDURES			S	U	N/A	N/C
53.	195.402(c) 195.422	Pipelines, and each pipeline segment that has been relocated, replaced, or otherwise changed, must be pressure tested without leakage (see .302(b) , (c) , and .305(b) for exceptions). .302(a) ***E&C MANUAL GENERAL WELDING PROCEDURES REPAIR OF WELDS***	X			
54.	480-93-420	Except for lines converted under §195.5 , the following pipelines may be operated without having been pressure tested per Subpart E and without having established MOP under 195.406(a)(5) [80% of the 4 hour documented test pressure, or 80% of the 4 hour documented operating pressure] .302(c)				
55.						
56.						

SUBPART E - PRESSURE TESTING PROCEDURES		S	U	N/A	N/C
57.	<p>- Intrastate liquid lines constructed before 10/21/85 (excluding HVL onshore or low stress lines). .302(b)(iii)</p> <p>- Carbon dioxide pipeline constructed before 07/12/91 that is located in a rural area as part of production field distribution system. .302(b)(2)(ii)</p> <p>- Any low-stress pipeline constructed before 8/11/1994, that does not transport HVL. .302(b)(3)</p> <p>- Those portions of older hazardous liquid and carbon dioxide pipelines for which an operator has elected the risk-based alternative under §195.303 and which are not required to be tested based on the risk-based criteria. .302(b)(4)/.303</p> <p><i>Note: (An operator that elected to follow a risk-based alternative must have developed plans that included the method of testing and a schedule for the testing by December 7, 1998. The compliance deadlines for completion of testing are as shown in the table in §195.303, and in no case was testing to be completed later than 12/07/2004).</i></p>				
58.	Have pipelines <u>other than those described above</u> been pressure tested per Subpart E? ***E&C MANUAL HYDROSTATIC TESTING REQUIREMENTS***	X			
59.	If pipelines <u>other than those described above</u> have not been pressure tested per Subpart E, has MOP been established under 195.406(a)(5) , in accordance with .302(c)?			X	
60.	<i>Note: Establishing MOP under 195.406(a)(5) only applies to specified "older" pipelines constructed prior to the dates in .302(b).</i>				
61.	Test pressure must be maintained for at least 4 continuous hours at a pressure equal to 125 percent, or more, of the MOP. If not visually inspected during the test, at least an additional 4 hours at 110 percent of MOP is required. .304 ***E&C MANUAL HYDROSTATIC TESTING REQUIREMENTS***	X			
62.	All pipe, all attached fittings, including components, must be pressure tested in accordance with §195.302 . .305(a) ***E&C MANUAL HYDROSTATIC TESTING REQUIREMENTS***	X			
63.	A component, other than pipe, that is the only item being replaced or added to the pipeline system need not be hydrostatically tested under paragraph (a) of this section if the manufacturer certifies that either: (1) The component was hydrostatically tested at the factory; or (2) The component was manufactured under a quality control system that ensures each component is at least equal in strength to a prototype that was hydrostatically tested at the factory. .305(b) ***E&C MANUAL HYDROSTATIC TESTING REQUIREMENTS***	X			
64.	Appropriate test medium .306 ***E&C MANUAL HYDROSTATIC TESTING REQUIREMENTS***	X			
65.	Pipe associated with tie-ins must be pressure tested. .308 ***E&C MANUAL HYDROSTATIC TESTING REQUIREMENTS***	X			
66.	Test records must be retained for useful life of the facility. .310(a) ***E&C MANUAL HYDROSTATIC TESTING REQUIREMENTS***	X			
67.	Does the record required by paragraph (a) of this section include: .310(b)				
68.	Pressure recording charts. .310(b)(1) ***E&C MANUAL HYDROSTATIC TESTING REQUIREMENTS***	X			
69.	Test instrument calibration data. .310(b)(2) ***E&C MANUAL HYDROSTATIC TESTING REQUIREMENTS***	X			
70.	Name of the operator, person responsible, test company used, if any. .310(b)(3) ***E&C MANUAL HYDROSTATIC TESTING REQUIREMENTS***	X			
71.	Date and time of the test. .310(b)(4) ***E&C MANUAL HYDROSTATIC TESTING REQUIREMENTS***	X			
72.	Minimum test pressure. .310(b)(5) ***E&C MANUAL HYDROSTATIC TESTING REQUIREMENTS***	X			
73.	Test medium. .310(b)(6) ***E&C MANUAL HYDROSTATIC TESTING REQUIREMENTS***	X			
74.	Description of the facility tested and the test apparatus. .310(b)(7) ***E&C MANUAL HYDROSTATIC TESTING REQUIREMENTS***	X			
75.	Explanation of any pressure discontinuities, including test failures, that appear on the pressure recording charts. .310(b)(8) ***E&C MANUAL HYDROSTATIC TESTING REQUIREMENTS***	X			

SUBPART E - PRESSURE TESTING PROCEDURES			S	U	N/A	N/C
74.		Where elevation differences in the test section exceed 100 feet , a profile of the elevation over entire length of the test section must be included. .310(b)(9) ***E&C MANUAL HYDROSTATIC TESTING REQUIREMENTS***	X			
75.		Temperature of the test medium or pipe during the test period. Amdt 195-78 pub. 9/11/03, eff. 10/14/03. .310(b)(10) ***E&C MANUAL HYDROSTATIC TESTING REQUIREMENTS***	X			
76.		Signature of certifying agent. WAC 480-75-420 (4)(b) ***E&C MANUAL HYDROSTATIC TESTING REQUIREMENTS***	X			
77.		Beginning and ending times of the test. WAC 480-75-420 (4)(c) ***E&C MANUAL HYDROSTATIC TESTING REQUIREMENTS***	X			
78.		Highest and lowest pressure achieved. WAC 480-75-420 (4)(e) ***E&C MANUAL HYDROSTATIC TESTING REQUIREMENTS***	X			
79.		Is report submitted to the commission 45 days prior to a hydro test, if test was used to raise the MOP (after 9/26/02)? WAC 480-75-620 ***E&C MANUAL HYDROSTATIC TESTING REQUIREMENTS***	X			

Comments:

59. All Targa Sound Terminal, LLC. pipelines have been pressure tested

SUBPART F - OPERATIONS & MAINTENANCE PROCEDURES			S	U	N/A	N/C
80.		a. Has the operator prepared a manual for normal operations & maintenance activities & handling abnormal operations & emergencies? .402 ***O&M MANUAL/E&C MANUAL***	X			
81.	195.402(a)	b. Procedures for reviewing the manual at intervals not exceeding 15 months, but at least each calendar year? ***O&M SEC 02 PAGE 5***	X			
82.		c. Appropriate parts must be kept at locations where O&M activities are conducted. ***O&M SEC 02 PAGE 5/MANUAL IS MAINTAINED IN CONTROL ROOM AND AVAILABLE ONLINE***	X			

Comments:

SUBPART F - MAINTENANCE & NORMAL OPERATION PROCEDURES			S	U	N/A	N/C
		Written procedures must be followed to provide safety during maintenance and normal operations. Does the operator have procedures for: .402(c)				
83.		Determining which pipeline facilities are located in areas that would require an immediate response by the operator to prevent hazards to the public if the facilities failed or malfunctioned? .402(c)(4) ***O&M SEC 07 PAGE 1***	X			
84.	195.402(a)	Analyzing pipeline accidents to determine their causes? .402 (c)(5) ***O&M SEC 08 PAGE 1***	X			
85.		Minimizing the potential for hazards identified under paragraph (c)(4) and minimizing the possibility of recurrence of accidents analyzed under paragraph (c)(5)? .402(c)(6) ***O&M SEC 08 PAGE 1***	X			
86.		Starting up and shutting down any part of the pipeline system in a manner designed to assure operation within limits prescribed by §195.406 , considering the hazardous liquid or carbon dioxide in transportation, variations in the altitude along the pipeline, and pressure monitoring and control devices? .402(c)(7) ***O&M SEC 09 PAGE 1***	X			

SUBPART F - MAINTENANCE & NORMAL OPERATION PROCEDURES			S	U	N/A	N/C
87.		A pipeline that is not equipped to fail safe monitoring from an attended location pipeline pressure during startup until steady state pressure and flow conditions are reached and during shut-in to assure operation within limits prescribed by §195.406? .402(c)(8) ***O&M SEC 10 PAGE 1***	X			
88.		Facilities not equipped to fail safe that are identified under §195.402(c)(4) or that control receipt and delivery of hazardous liquid, detecting abnormal operating conditions by monitoring pressure, temperature, flow or other appropriate operational data and transmitting this data to an attended location? .402(c)(9) ***O&M SEC 10 PAGE 1***	X			
89.		Abandoning pipeline facilities, including safe disconnection from an operating pipeline system, purging of combustibles, and sealing abandoned environmental hazards .402(c)(10) ***O&M SEC 4.2 PAGE 1***	X			
90.		Reporting abandoned pipeline facilities offshore, or onshore crossing commercially navigable waterways per 195.59. ***O&M SEC 4.1 PAGE 1***	X			
91.		Minimizing the likelihood of accidental ignition of vapors in areas near facilities identified under paragraph (c)(4) of this section where the potential exists for the presence of flammable liquids or gases? .402(c)(11) ***O&M SEC 11 PAGE 1***	X			
92.		Establishing and maintaining liaison with fire, police, and other appropriate public officials to learn the responsibility and resources of each hazardous liquid pipeline emergency. .402(c)(12) ***O&M SEC 12 PAGE 1***	X			
93.		Periodically reviewing the work done by operator's personnel to determine the effectiveness of the procedures used in normal operation and maintenance and taking corrective action where deficiencies are found? .402(c)(13) ***O&M SEC 13 PAGE 1***	X			
94.		Taking adequate precautions in excavated trenches to protect personnel from hazards of unsafe accumulations of vapor or gas, making available when needed at the excavation site, emergency rescue equipment, including a breathing apparatus and, a rescue harness and line. .402(c)(14) ***O&M SEC 13 PAGE 1***	X			

Comments:

MAINTENANCE & NORMAL OPERATION PROCEDURES CONT:			S	U	N/A	N/C
95.	.402(c)(15)	Implementing the applicable control room management procedures required by 195.446. (Amdt. 195-93, 74 FR 63310, December 3, 2009, eff. 2/1/2010). .402(c)(15) ***CRM PLAN***	X			
96.	480-75-300	Providing leak detection under flow and no flow conditions and including a procedure for responding to alarm ***O&M SEC 29 PAGE 1***	X			
97.	480-75-330	Responding to breakout tank overfill alarms ***O&M SEC 29 PAGE 1***	X			
98.	480-75-400	Backfilling pipe ***E&C PAGE 27 BACKFILLING***	X			
99.	480-75-410	Using a holiday detector to check coating condition prior to backfilling ***E&C PAGE 26 INSPECTION AND REPAIR OF COATING***	X			
100.	480-75-460	100% Inspection of welds. ***E&C PAGE 18 WELDS: NONDESTRUCTIVE TESTING AND RETENTION OF TESTING RECORDS***	X			
101.	480-75-550	Reviewing change in class location for pipelines installed after 9/26/2003. ***O&M SEC 05 PAGE 6***	X			

ABNORMAL OPERATION PROCEDURES (CONTROL CENTER FUNCTION)			S	U	N/A	N/C
	195.402(a)	The O&M manual must contain written procedures to provide safety when operating design limits have been exceeded. Does the operator have procedures for: .402(d)				
		Responding to, investigating, and correcting the cause of: .402(d)(1)				

ABNORMAL OPERATION PROCEDURES (CONTROL CENTER FUNCTION)			S	U	N/A	N/C
102.		i. Unintended closure of valves or shutdowns? ***ABNORMAL OPERATIONS SECTION A 2(a)***	X			
103.		ii. An increase or decrease in pressure or flow rate outside normal operating limits? ***ABNORMAL OPERATIONS SECTION A 2(b)***	X			
104.		iii. Loss of communications? ***ABNORMAL OPERATIONS SECTION A 2(c)***	X			
105.		iv. The operation of any safety device? ***ABNORMAL OPERATIONS SECTION A 2(d)***	X			
106.		v. Any other malfunction of a component, deviation from normal operation, or personnel error which could cause a hazard to persons or property? ***ABNORMAL OPERATIONS SECTION A 2(e)***	X			
107.		Checking variations from normal operation after abnormal operations have ended at sufficient critical locations in the system to determine continued integrity and safe operations? .402(d)(2) ***ABNORMAL OPERATIONS SECTION B 2***	X			
108.		Correcting variations from normal operation of pressure and flow equipment controls? .402(d)(3) ***ABNORMAL OPERATIONS SECTION C***	X			
109.		Does operating personnel notify responsible operator personnel where notice of an abnormal operation is received? .402(d)(4) ***ABNORMAL OPERATIONS SECTION D***	X			
110.		Periodically reviewing the response of operating personnel to determine the effectiveness of the procedures and taking corrective action where deficiencies are found? .402(d)(5) ***ABNORMAL OPERATIONS SECTION E***	X			

Comments:

EMERGENCY PROCEDURES			S	U	N/A	N/C
		The O&M manual must include written procedures to provide safety when an emergency condition occurs. Does the operator have procedures for: .402(e)				
111.		Receiving, identifying, and classifying notices of events which need immediate response by the operator or fire, police, or other, and notifying appropriate operator's personnel for corrective action? .402(e)(1) ***ERP MANUAL SEC IV C*** Note: Including third-party damage	X			
112.	195.402(a)	Making a prompt and effective response to a notice of each type of emergency, fire, explosion, accidental release of hazardous liquid, operational failure, natural disaster affecting the pipeline? .402(e)(2) ***ERP MANUAL SEC IV C*** Note: Including third party damage	X			
113.		Making personnel, equipment, instruments, tools, and materials available at the scene of an emergency? .402(e)(3) ***ERP MANUAL SEC IV B***	X			
114.		Taking action; such as emergency shutdown or pressure reduction, to minimize release of liquid at a failure site? .402(e)(4) ***ERP MANUAL SEC IV U***	X			
115.		Controlling the release of liquid at the failure site? .402(e)(5) ***ERP MANUAL SEC IV S***	X			
116.	195.402(a)	Minimizing the public .402(e)(6) exposure and accidental ignition, evacuation, and halting traffic on roads, railroads, etc.? ***ERP MANUAL SEC IV S***	X			
117.		Notifying fire, police, and others of hazardous liquid emergencies and preplanned responses including HVLs ? .402(e)(7) ***ERP MANUAL SEC IV H***	X			
118.		Determining extent and coverage of vapor cloud and hazardous areas of HVLs by using appropriate instruments? .402(e)(8)			X	
119.		Post-accident review of employee's activities to determine if procedures were effective and corrective action was taken? .402(e)(9) ***ERP MANUAL SEC IV N***	X			
120.		Actions to be taken by a controller during an emergency in accordance with 195.446 , (Amdt. 195-93, 74 FR 63310, December 3, 2009, eff. 2/1/2010). .402(e)(10) ***ERP MANUAL SEC IV U***	X			

Comments:

Comments:

118. Targa Sound Terminal, LLC. does not transport HVL's.

EMERGENCY RESPONSE TRAINING PROCEDURES (CONTROL CENTER & FIELD)			S	U	N/A	N/C	
		Each operator shall establish and conduct a written continuing training program to instruct operating and maintenance personnel to: .403(a)					
121.	195.402(a)	Carry out the emergency response procedures established under §195.402. .403(a)(1) ***ERP MANUAL SEC IV O***	X				
122.		Know the characteristics and hazards of liquids or carbon dioxide transported, including in the case of HVL, flammability, of mixtures with air, odorless vapors, and water reactions. .403(a)(2) ***ERP MANUAL SEC IV O***	X				
123.		Recognize conditions that are likely to cause emergencies; predict the consequences of malfunction or failures and take appropriate actions. .403(a)(3) ***ERP MANUAL SEC IV O***	X				
124.		Take steps necessary to control any accidental release of hazardous liquid or carbon dioxide and to minimize the potential for fire, explosion, toxicity, or environmental damage. .403(a)(4) ***ERP MANUAL SEC IV O***	X				
125.		Learn the potential causes, types, sizes, and consequences of fire and the appropriate use of portable fire extinguishers and other on-site fire control equipment, involving, where feasible, a simulated pipeline emergency condition. .403(a)(5) ***ERP MANUAL SEC IV O***	X				
126.		Instructions to enable O&M personnel to recognize and report potential safety related conditions. .402(f) ***ERP MANUAL SEC IV O***	X				
			At intervals not exceeding 15 months, but at least once each calendar year: .403(b)				
127.			Review with personnel their performance in meeting the objectives of the emergency response training program .403(b)(1) ***ERP MANUAL SEC IV O***	X			
128.			Make appropriate changes to the emergency response training program .403(b)(2) ***ERP MANUAL SEC IV O***	X			
129.			Require and verify that supervisors maintain a thorough knowledge of the emergency response procedures for which they are responsible. .403(c) ***ERP MANUAL SEC IV O***	X			

Comments:

MAPS and RECORDS PROCEDURES			S	U	N/A	N/C
130.	195.402(a) & WAC 480-75-600	Making construction records, maps, and operating history available as necessary for safe operation and maintenance. .402(c)(1) ***O&M SEC 05 PAGE 1/MAPS MADE BY SITTS & HILL***	X			
		Each operator shall maintain current maps and records of its pipeline system that include at least the following information: .404(a) Updated within 6 months 480-75-600				
		Location and identification of the following facilities: .404(a)(1) ***O&M SEC 05 PAGE 1/MAPS AND PLANS MADE BY SITTS & HILL***				
131.		i. Breakout tanks	X			
132.		ii. Pump stations	X			
133.		iii. Scraper and sphere facilities	X			
134.		iv. Pipeline valves	X			
135.		v. Facilities to which §195.402(c)(9) applies	X			
136.	vi. Rights-of-way	X				

MAPS and RECORDS PROCEDURES			S	U	N/A	N/C
137.		vii. Safety devices to which §195.428 applies	X			
138.		All crossings of public roads, railroads, rivers, buried utilities and foreign pipelines. .404(a)(2) ***O&M SEC 05 PAGE 1/MAPS AND PLANS MADE BY SITTS & HILL***	X			
139.		The maximum operating pressure of each pipeline. .404(a)(3) ***O&M SEC 05 PAGE 1/MAPS AND PLANS MADE BY SITTS & HILL***	X			
140.		The diameter, grade, type, and nominal wall thickness of all pipe. .404(a)(4) ***O&M SEC 05 PAGE 1/MAPS AND PLANS MADE BY SITTS & HILL***	X			
		Each operator shall maintain for at least 3 years daily operating records for the following: .404(b)				
141.		The discharge pressure at each pump station. .404(b)(1) ***O&M SEC 05 PAGE 2***	X			
142.		Any emergency or abnormal operation to which the procedures under §195.402 apply. .404(b)(2) ***O&M SEC 05 PAGE 2***	X			
		Each operator shall maintain the following records for the periods specified: .404(c)				
143.		The date, location, and description of each repair made on the pipe and maintain it for the life of the pipe . .404(c)(1) ***O&M SEC 05 PAGE 2***	X			
144.		The date, location, and description of each repair made to parts of the pipeline system other than the pipe and maintain it for at least 1 year . .404(c)(2) ***O&M SEC 05 PAGE 2***	X			
145.		Each inspection and test required by Subpart F shall be maintained for at least 2 years, or until the next inspection or test is performed, whichever is longer . .404(c)(3) ***O&M SEC 05 PAGE 2***	X			

Comments:

MAXIMUM OPERATING PRESSURE PROCEDURES (MOP) - ALL SYSTEMS			S	U	N/A	N/C
		Except for surge pressures and other variations from normal operations, the MOP may not exceed any of the following: .406(a)				
146.		The internal design pressure of the pipe determined by §195.106. Amt. 195-86 Pub. 06/09/06 eff. 07/10/06 .406(a)(1) ***E&C MANUAL PIPE DESIGN***	X			
147.		The design pressure of any other component on the pipeline. .406(a)(2) ***E&C MANUAL PIPE DESIGN***	X			
148.		80% of the test pressure (Subpart E). .406(a)(3) ***E&C MANUAL PIPE DESIGN***	X			
149.	195.402(a)	80% of the factory test pressure or of the prototype test pressure for any individual component. .406(a)(4) ***E&C MANUAL PIPE DESIGN***	X			
150.		80% of the test pressure or the highest operating pressure for a minimum of 4 hours for a pipeline that has not been tested under Subpart E . .406(a)(5)			X	
151.		The pipeline may not be operated at a pressure that exceeds 110% of the MOP during surges or other variations from normal operations: .406(b) ***O&M SEC 16 PAGE 2***	X			
152.		Adequate controls and protective equipment must be installed to prevent the pressure from exceeding 110% of the MOP. ***O&M SEC 16 PAGE 2***	X			

Comments:

150. All Targa Sound Terminal, LLC. pipe have been tested under subpart E

COMMUNICATION PROCEDURES (CONTROL CENTER)			S	U	N/A	N/C
-------------------------------------------	--	--	---	---	-----	-----

COMMUNICATION PROCEDURES (CONTROL CENTER)			S	U	N/A	N/C
153.	.402(a)	Operator must have a communication system to provide for the transmission of information needed for the safe operation of its pipeline system. .408(a) ***O&M SEC 18 PAGE 1***	X			
		Does the communication system required by paragraph (a) include means for: .408(b)				
154.		Monitoring operational data as required by §195.402(c)(9) . .408(b)(1) ***O&M SEC 18 PAGE 1***	X			
155.		Receiving notices from operator personnel, the public, and others about abnormal or emergency conditions and initiating corrective actions. .408(b)(2) ***O&M SEC 18 PAGE 1***	X			
156.		Conducting two-way vocal communication between a control center and the scene of abnormal operations and emergencies. .408(b)(3) ***O&M SEC 18 PAGE 1***	X			
157.		Providing communication with fire, police, and other appropriate public officials during emergency conditions, including a natural disaster. .408(b)(4) ***O&M SEC 18 PAGE 1***	X			

Comments:

LINE MARKER PROCEDURES			S	U	N/A	N/C
158.	480-75-540	Markers checked annually and replaced within 30 days ***O&M SEC 19 PAGE 3***	X			
159.	195.402(a)	Line markers must be placed over each buried pipeline in accordance with the following: .410(a) ***O&M SEC 19 PAGE 3***	X			
160.		Located at each public road crossing, railroad crossing, and sufficient number along the remainder of each buried line so that its location is accurately known .410(a)(1) ***O&M SEC 19 PAGE 3***	X			
161.		Must have the correct characteristics and information .410(a)(2) ***O&M SEC 19 PAGE 3***	X			
162.		Must be placed where pipelines are aboveground in areas that are accessible to the public .410(c) ***O&M SEC 19 PAGE 3***	X			

Comments:

INSPECTION RIGHTS-of -WAY & CROSSINGS UNDER NAVIGABLE WATER PROCEDURES			S	U	N/A	N/C
163.	480-75-540	Depth of Cover - For pipelines constructed after 4/1/70, depth of cover surveys every five years or every three years for areas subject to erosion or subsoiling ***O&M SEC 05 PAGE 5***	X			
164.	195.402(a)	Operator must inspect the right-of-way weekly (unless weather impedes flyovers when applicable) WAC 480-75-530 ***O&M SEC 20 PAGE 1***	X			
165.		Operator must inspect each crossing under a navigable waterway to determine the crossing condition at intervals not exceeding 5 years. .412(b) ***O&M SEC 20 PAGE 2***	X			

Comments:

Comments:

UNDERWATER INSPECTION PROCEDURES of OFFSHORE PIPELINES			S	U	N/A	N/C
		When the operator discovers that a pipeline it operates is exposed on the seabed or constitutes a hazard to navigation, does the operator: .413(c)				
166.	195.402(a)	Promptly, but no later than 24 hours after discovery, notify the NRC by phone. .413(c)(1)			X	
167.		Promptly, but not later than 7 days after discovery, mark the location of the pipeline in accordance with 33 CFR Part 64 at each end of the pipeline segment and at intervals of not over 500 yards long , except that a pipeline segment less than 200 yards long need only be marked at the center. .413(c)(2)			X	
168.		Within 6 months after discovery, or not later than November 1 of the following year if the 6 month period is after November 1 of that year the discovery is made, place the pipeline so that the top of the pipe is 36 inches below the seabed for normal excavation or 18 inches for rock excavation. .413(c)(3)			X	
169.		Offshore pipeline condition reports - must be filed within 60 days after the inspections .57			X	

Comments:
166-169. Targa Sound Terminal, LLC. does not operate offshore.

VALVE MAINTENANCE PROCEDURES			S	U	N/A	N/C
170.	195.402(a)	Operator must maintain each valve that is necessary for the safe operation of its pipeline system in good working order at all times. .420(a) ***O&M SEC 21 PAGE 1***	X			
171.		Operator must inspect each mainline valve to determine that it is functioning properly at intervals not exceeding 7 1/2 months , but at least twice each calendar year. .420(b) ***O&M SEC 21 PAGE 1***	X			
172.		Operator must provide protection for each valve from unauthorized operation and from vandalism. .420(c) ***O&M SEC 21 PAGE 2***	X			

Comments:
.

PIPELINE REPAIR PROCEDURES			S	U	N/A	N/C
173.	WAC 480-75-440	Repairs made in accordance with ASME B31.4 ***O&M SEC 22.1 PAGE 2***	X			
174.	195.402(a)	Operator must, in repairing its pipeline systems, insure that the repairs are made in a safe manner and are made so as to prevent damage to persons and property. .422(a) ***O&M SEC 22.1 PAGE 1***	X			
175.		No operator may use any pipe, valve, or fitting, for replacement in repairing pipeline facilities, unless it is designed and constructed as required by this part. .422(b) ***O&M SEC 22.1 PAGE 1***	X			

Comments:

PIPE MOVEMENT PROCEDURES			S	U	N/A	N/C
176.	480-75-500	For evaluating pipe conditions during pipe movement including API 1117 stress calculations? ***O&M SEC 23 PAGE 1***	X			
177.	195.402(a)	When moving any pipeline, the operator must reduce the pressure for the line segment involved to 50% of the MOP . .424(a) ***O&M SEC 23 PAGE 1***	X			
		For HVL lines joined by welding, the operator must: .424(b)				
178.		Move the line when it does not contain HVL , unless impractical. .424(b)(1)			X	
179.		Have procedures under §195.402 containing precautions to protect the public. .424(b)(2)			X	
180.		Reduce the pressure for the line segment involved to the lower of 50% of the MOP or the lowest practical level that will maintain the HVL in a liquid state. (Minimum = V.P. + 50 psig) .424(b)(3)			X	
		For HVL lines not joined by welding, the operator must: .424(c)				
181.		Move the line when it does not contain HVL , unless impractical. .424(c)(1)			X	
182.		Have procedures under §195.402 containing precautions to protect the public. .424(c)(2)			X	
183.	Isolate the line to prevent flow of the HVL . .424(c)(3)			X		

Comments:

178-183. Targa Sound Terminal, LLC. does not transport HVLs.

SCRAPER and SPHERE FACILITY PROCEDURES			S	U	N/A	N/C
184.	195.402(a)	Operator must have a relief device capable of safely relieving the pressure in the barrel before insertion or removal of scrapers or spheres. .426***O&M SEC 24/APPENDIX 1-13 LAUNCHER RECIVER PLAN***	X			
185.		Operator must have a suitable device to indicate that pressure has been relieved, or a means to prevent insertion. ***O&M SEC 24/APPENDIX 1-13 LAUNCHER RECIVER PLAN***	X			

Comments:

OVERPRESSURE SAFETY DEVICE PROCEDURES			S	U	N/A	N/C
186.	195.402(a)	Operator must inspect and test each pressure limiting device, relief valve, pressure regulator, or other items of pressure control equipment to determine that it is functioning properly, in good mechanical condition, has adequate capacity, and is reliable. .428(a) ***O&M SEC 26 PAGE 1***	X			
		Operator must inspect and test overpressure safety devices at the following intervals:				
187.		1. Non-HVL pipelines at intervals not to exceed 15 months , but at least once each calendar year. ***O&M SEC 26 PAGE 1***	X			
188.		2. HVL pipelines at intervals not to exceed 7-1/2 months , but at least twice each calendar year.			X	
189.		Operator must inspect and test relief valves on HVL breakout tanks at intervals not exceeding 5 years . .428(b)			X	

OVERPRESSURE SAFETY DEVICE PROCEDURES			S	U	N/A	N/C
190.		Aboveground breakout tanks that are constructed or significantly altered according to API Standard 2510 after October 2, 2000, must have an overflow protection system installed according to section 5.1.2 of API Standard 2510.	X			
		Tanks over 600 gallons (2271 liters) constructed or significantly altered after October 2, 2000, must have overflow protection according to API Recommended Practice 2350 unless operator noted in procedures manual (§195.402) why compliance with API RP 2350 is not necessary for the safety of a particular breakout tank. .428(c) ***APPENDIX 1-11***				
191.		After October 2, 2000, the requirements of paragraphs (a) and (b) of this section for inspection and testing of pressure control equipment apply to the inspection and testing of overflow protection systems. .428(d) ***APPENDIX 1-11***	X			

Comments:

188-189. Targa Sound Terminal, LLC. does not transport HVLs.

FIREFIGHTING EQUIPMENT PROCEDURES			S	U	N/A	N/C
192.		Operator must maintain adequate firefighting equipment at each pump station and breakout tank areas. .430 (a-c) ***O&M SEC 25 PAGE 1***	X			
		The equipment must be:				
193.	195.402(a)	a. In proper operating condition at all times. ***O&M SEC 25 PAGE 1***	X			
194.		b. Plainly marked so that its identity as firefighting equipment is clear. ***O&M SEC 25 PAGE 1***	X			
195.		c. Located so that it is easily accessible during a fire. ***O&M SEC 25 PAGE 1***	X			

Comments:

BREAKOUT TANK PROCEDURES		
196.	195.402(a)	Utilize PHMSA Form #10 for all Breakout Tank Procedures ***APPENDIX 1-11***

SIGN PROCEDURES			S	U	N/A	N/C
197.		Operator must maintain signs visible to the public around each pumping station and breakout tank area. ***APPENDIX 1-2/1-3***	X			
198.	.402(a)	.434 Signs must contain the name of the operator and a telephone number (including area code) where the operator can be reached at all times. Amdt 195-78 pub. 9/11/03, eff. 10/14/03. ***APPENDIX 1-3***	X			

Comments:

SECURITY of FACILITY PROCEDURES			S	U	N/A	N/C
199.	195.402(a)	Operator must provide protection for each pumping station and breakout tank area and other exposed facilities from vandalism and unauthorized entry. .436***APPENDIX 1-3***	X			

Comments:

Comments:

SMOKING OR OPEN FLAME PROCEDURES			S	U	N/A	N/C
200.	195.402(a)	Operator must prohibit smoking and open flames in each pump station and breakout tank area where there is the possibility of the presence of hazardous liquids or flammable vapors. .438***APPENDIX 1-3***	X			

Comments:

PUBLIC AWARENESS PROGRAM PROCEDURES (Also in accordance with API RP 1162)			S	U	N/A	N/C
1.	192.402(a)	Public Awareness Program in accordance with API RP 1162, (1 st edition Dec-2003) .440				
2.		The operators program must specifically include provisions to educate the public, appropriate government organizations, and persons engaged in excavation related activities on: .440(d)				
3.		(1) Use of a one-call notification system prior to excavation and other ***O&M SEC 17 PAGE 1***	X			
4.		(2) Possible hazards associated with unintended releases from a hazardous liquids or carbon dioxide pipeline facility; ***PA PLAN***	X			
5.		(3) Physical indications of a possible release; ***PA PLAN***	X			
6.		(4) Steps to be taken for public safety in the event of a hazardous liquid or carbon dioxide pipeline release; ***PA PLAN***	X			
7.		(5) Procedures to report such an event (to the operator). ***PA PLAN***	X			
8.		Does program include activities to advise affected municipalities, school districts, businesses, and residents of pipeline facility locations. .440(e) ***PA PLAN***	X			
9.		The operator's program and the media used must be comprehensive enough to reach all areas the operator transports gas. .440(f) ***PA PLAN***	X			
10.		Is the program conducted in English and any other languages commonly understood by a significant number of the population? .440(g) ***PA PLAN***	X			
11.		IAW API RP 1162, the operator's program should be reviewed for effectiveness within four years of the date the operator's program was first completed. For operators in existence on June 20, 2005, who must have completed their written programs no later than June 20, 2006, the first evaluation is due no later than June 20, 2010. .440(i) ***PA PLAN***	X			

Comments:

DAMAGE PREVENTION PROGRAM PROCEDURES (Also in accordance with API 1162)			S	U	N/A	N/C
201.	.402(a)	.442(a) Is there a written program in place to prevent damage by excavation activities applicable to the operator's pipelines? ***O&M SEC 17 PAGE 2***	X			
202.		.442(b) Does the operator participate in a qualified One-Call program? ***O&M SEC 17 PAGE 2***	X			
203.		.442(c)(1) Include the identity, on a current basis, of persons who normally engage in excavation activities in the area in which the pipeline is located. ***PA PLAN***	X			
		.442(c)(2) Provide for notification to the public in the vicinity of the pipeline and actual notification to the persons identified in paragraph (c)(1) of this section of the following, as often as needed to make them aware of the damage prevention program:				

DAMAGE PREVENTION PROGRAM PROCEDURES (Also in accordance with API 1162)				S	U	N/A	N/C	
204.		i.	The program's existence and purpose. ***PA PLAN***	X				
205.		ii.	How to learn the location of underground pipelines before excavation activities are begun. ***PA PLAN***	X				
206.	.442(c)(3)		Provide a means of receiving and recording notification of planned excavation activities. ***O&M SEC 17 PAGE 2***	X				
207.	.442(c)(4)		If the operator has buried pipelines in the area of excavation activity, provide for actual notification of persons who give notice of their intent to excavate of the type of temporary marking to be provided and how to identify the markings. ***O&M SEC 17 PAGE 2***	X				
208.	.442(c)(5)		Provide for marking of buried pipelines in the area of excavation activity within 2 business days. WAC 480-75-270 RCW 19.122.030***O&M SEC 17 PAGE 1***	X				
			Provide as follows for inspection of pipelines that an operator has reason to believe could be damaged by excavation activities:					
209.	.442(c)(6)	i.	The inspection must be done as frequently as necessary during and after the activities to verify the integrity of the pipeline. ***O&M SEC 17 PAGE 3***	X				
210.		ii.	In the case of blasting, any inspection must include leakage surveys. ***O&M SEC 17 PAGE 4***	X				
211.			Does the operator have directional drilling/boring procedures which include taking actions necessary to protect their facilities from the dangers posed by drilling and other trenchless technologies? ***O&M SEC 17 PAGE 3***	X				
			Does the operator review records of accidents and failures due to excavation damage to ensure causes of failures are addressed to minimize the possibility of reoccurrence? ***O&M SEC 17 PAGE 5***	X				
212.		Damage Prevention (Operator Internal Performance Measures) PHMSA – State Program Evaluation Questions						
213.				Does the operator have a quality assurance program in place for monitoring the locating and marking of facilities? Do operators conduct regular field audits of the performance of locators/contractors and take action when necessary? (CGA Best Practices v. 6.0, Best Practice 4-18. Recommended only, not required)	X			
214.				Does operator including performance measures in facility locating services contracts with corresponding and meaningful incentives and penalties?	X			
215.				Do locate contractors address performance problems for persons performing locating services through mechanisms such as re-training, process change, or changes in staffing levels?	X			
216.			Does the operator periodically review the Operator Qualification plan criteria and methods used to qualify personnel to perform locates?	X				
217.			Review operator locating and excavation <u>procedures</u> for compliance with state law and regulations.	X				
218.			Are locates are being made within the timeframes required by state law and regulations? Examine record sample.	X				
219.			Are locating and excavating personnel properly <u>qualified</u> in accordance with the operator's Operator Qualification plan and with federal and state requirements?	X				

DAMAGE PREVENTION PROGRAM PROCEDURES (State Requirements)				S	U	N/A	N/C
220.	Terminating the flow of hazardous liquid in pipeline immediately upon receiving information of <u>third party damage. RCW 19.122.035 (2) ***O&M SEC 17 PAGE 5***</u>			X			
221.	Has the pipeline company visually inspected the damaged pipeline RCW 19.122.035 (2) ***O&M SEC 17 PAGE 5***			X			
222.	Has the pipeline company determined if the damaged pipeline should be repaired or replaced RCW 19.122.035 (2) ***O&M SEC 17 PAGE 5***			X			
223.	Notification to local first responders and Dept of Ecology of any reportable release? ***O&M SEC 17 PAGE 6***			X			

Comments:

Comments:

CPM/LEAK DETECTION PROCEDURES			S	U	N/A	N/C
224.	.402(a)	Each new computational pipeline monitoring (CPM) leak detection system and each replaced component of an existing CPM system must comply with section 4.2 of API 1130, (3rd Edition, September 2007) in its design and with any other design criteria addressed in API 1130 for components of the CPM leak detection system. (Amdt 195-94 Pub. 75 FR 48593 8/11/10 eff. 10/01/10). .134***O&M SEC 29 PAGE 1***	X			
225.		If a CPM system is installed, operator's procedures for the CPM leak detection system shall comply with API 1130, (3rd Edition, September 2007) in operating, maintaining, testing, record keeping, and dispatching training. (Amdt 195-94, 75 FR 48593 Pub. 8/11/10 eff. 10/01/10). .444; .446(b)(c) ***O&M SEC 29 PAGE 1***	X			

Comments:

CONTROL ROOM MANAGEMENT PROCEDURES (Amdt. 195-93, 74 FR 63310, December 3, 2009, eff. 2/1/2010)			S	U	N/A	N/C
.402(a)	.446	This section applies to each operator of a pipeline facility with a controller working in a control room who monitors and controls all or part of a pipeline facility through a SCADA system.				
	.446(a)	Operator must develop written procedures no later than August 1, 2011, and implement the procedures no later than February 1, 2013. Amdt. 195-93 Pub. 12/03/09 eff. 02/01/10, ***CRM MANUAL***	X			
	.446(b)	Operator must define roles and responsibilities of a controller during normal, abnormal, and emergency operating conditions including: (1) When making decisions and taking actions during normal operations; (2) When an abnormal operating condition is detected; (3) During an emergency; (4) A method of recording controller shift-changes and any hand-over of responsibility between controllers. ***CRM MANUAL PAGE 2, 3, 10***	X			
	.446(c)(1)	Operator must implement API RP 1165, (1st Edition, January 2007) (incorporated by reference, <i>see</i> § 195.3) whenever a SCADA system is added, expanded or replaced, unless the operator demonstrates that certain provisions of API RP 1165 are not practical for the SCADA system used. ***CRM MANUAL PAGE 6***	X			
	.446(c)(2)	Operator must conduct a point-to-point verification between SCADA displays and related field equipment when field equipment is added or moved and when other changes that affect pipeline safety are made to field equipment or SCADA displays. ***CRM MANUAL PAGE 7***	X			
	.446(c)(3)	Operator must test and verify an internal communication plan to provide adequate means for manual operation of the pipeline safely, once each calendar year, NTE 15 months. ***CRM MANUAL PAGE 8***	X			
	.446(c)(4)	Operator must test any backup SCADA systems once each calendar year, NTE 15 months. ***CRM MANUAL PAGE 9***	X			
	.446(c)(5)	Operator must implement section 5 of API RP 1168, (1st Edition, September 2008) (incorporated by reference, <i>see</i> § 195.3) to establish procedures for when a different controller assumes responsibility, including the content of information to be exchanged. ***CRM MANUAL PAGE 10***	X			
.446(d)	Operator must implement the following methods to reduce the risk associated with controller fatigue that could inhibit a controller's ability to carry out the defined roles and responsibilities:					

CONTROL ROOM MANAGEMENT PROCEDURES (Amdt. 195-93, 74 FR 63310, December 3, 2009, eff. 2/1/2010)		S	U	N/A	N/C
	<ul style="list-style-type: none"> (1) Establish shift lengths and schedule rotations that provide controllers off-duty time sufficient to achieve eight hours of continuous sleep; (2) Educate controllers and supervisors in fatigue mitigation strategies and how off-duty activities contribute to fatigue; (3) Train controllers and supervisors to recognize the effects of fatigue; and (4) Establish a maximum limit on controller hours-of-service, which may provide for an emergency deviation from the maximum limit if necessary for the safe operation of a pipeline facility. ***CRM MANUAL PAGE 12*** 	X			
.446 (e)	<p>If a SCADA system is used, operator must have a written Alarm Management Plan including the following provisions to:</p> <ul style="list-style-type: none"> (1) Review SCADA safety-related alarm operations using a process that ensures alarms are accurate and support safe pipeline operations; (2) Identify at least once each calendar month points affecting safety that have been taken off scan in the SCADA host, have had alarms inhibited, generated false alarms, or that have had forced or manual values for periods of time exceeding that required for associated maintenance or operating activities; (3) Verify the correct safety-related alarm set-point values and alarm descriptions when associated field instruments are calibrated or changed and once each calendar year, NTE 15 months; (4) Review the alarm management plan required by this paragraph once each calendar year, NTE 15 months, to determine the effectiveness of the plan; (5) Monitor the content and volume of general activity being directed to and required of each controller once each calendar year, NTE 15 months, that will assure controllers have sufficient time to analyze and react to incoming alarms; and (6) Address deficiencies identified through the implementation of paragraphs (e)(1) through (e)(5) of this section. ***CRM MANUAL PAGE 23, 24*** 	X			
.446 (f)	<p>Assure changes that could affect control room operations are coordinated with the control room personnel by performing each of the following:</p> <ul style="list-style-type: none"> (1) Implement section 7 of API RP 1168 for control room management change and require coordination between control room representatives, operator's management, and associated field personnel when planning and implementing physical changes to pipeline equipment or configuration; and (2) Require field personnel to contact the control room when emergency conditions exist and when making field changes that affect control room operations. ***CRM MANUAL PAGE 10, 16*** 	X			
.446 (g)	<p>Assure lessons learned from operating experience are incorporated, as appropriate, into control room management procedures by performing each of the following:</p> <ul style="list-style-type: none"> (1) Review accidents that must be reported pursuant to § 195.50 and 195.52 to determine if control room actions contributed to the event and, if so, correct, where necessary, deficiencies related to: <ul style="list-style-type: none"> (i) Controller fatigue; (ii) Field equipment; (iii) The operation of any relief device; (iv) Procedures; (v) SCADA system configuration; and (vi) SCADA system performance. (2) Include lessons learned from the operator's experience in the training program required by this section. ***CRM MANUAL PAGE 18*** 	X			
.446 (h)	Operator must establish a controller training program to provide for training each controller to carry out the roles and responsibilities defined by the operator and review the training program content to identify potential improvements once each calendar year, NTE 15 months. ***CRM MANUAL PAGE 19***	X			
.446(h)	An operator's controller training program must include the following elements:				

CONTROL ROOM MANAGEMENT PROCEDURES (Amdt. 195-93, 74 FR 63310, December 3, 2009, eff. 2/1/2010)			S	U	N/A	N/C
		(1) Responding to abnormal operating conditions likely to occur simultaneously or in sequence; (2) Use of a computerized simulator or non-computerized (tabletop) method for training controllers to recognize abnormal operating conditions; (3) Training controllers on their responsibilities for communication under the operator's emergency response procedures; (4) Training that will provide a controller a working knowledge of the pipeline system, especially during the development of abnormal operating conditions; and (5) For pipeline operating setups that are periodically, but infrequently used, providing an opportunity for controllers to review relevant procedures in advance of their application. ***CRM MANUAL PAGE 19***	X			

Required Submission of Data to the National Pipeline Mapping System Under the Pipeline Safety Improvement Act of 2002			S	U	N/A	N/C
49 U.S.C. 60132, Subsection (b) ADB-08-07	Updates to NMPS: Operators are required to make update submissions every 12 months if any system modifications have occurred. Go to https://www.npms.phmsa.dot.gov/DataReview/login.jsp to review existing data on record. Also report no modifications if none have occurred since the last complete submission. Include operator contact information with all updates. ***O&M SEC 5 PAGE 2***	X				
RCW 81.88.080	Pipeline Mapping System: Operator provides accurate maps (or updates) of pipelines, operating over two hundred fifty pounds per square inch gauge, to specifications developed by the commission sufficient to meet the needs of first responders? ***O&M SEC 5 PAGE 2***	X				

PIPELINE INTEGRITY MANAGEMENT IN HIGH CONSEQUENCE AREAS PROCEDURES			S	U	N/A	N/C
.452	This form does not cover Liquid Pipeline Integrity Management Programs					

SUBPART G - OPERATOR QUALIFICATION PROCEDURES			S	U	N/A	N/C
.501 -.509	Refer to Operator Qualification Inspection Forms and Protocols (OPS web page)					

SUBPART H - CORROSION CONTROL PROCEDURES 195.402(a)			S	U	N/A	N/C
226.	195.402(a)	Do procedures require that supervisors maintain a thorough knowledge of that portion of the corrosion control procedures for which they are responsible for insuring compliance? .555***CORROSION CONTROL PLAN QUALIFICATIONS OF SUPERVISORS***	X			
227.		Except bottoms of aboveground breakout tanks, each buried or submerged pipeline must have an external coating for external corrosion control if the pipeline is : .557 a) Constructed, relocated, replaced, or otherwise changed after the applicable dates : 3/31/70 - interstate pipelines excluding low stress 7/31/77 -interstate offshore gathering excluding low stress 10/20/85-intrastate pipeline excluding low stress 7/11/91- carbon dioxide pipelines 8/10/94 - low stress pipelines NOTE: This does not include the movement of pipe under 195.424. ***CORROSION CONTROL PLAN EXTERNAL COATED PIPELINES***	X			
228.		b) Converted under 195.5 and 1) Has an external coating that substantially meets 195.559 before the pipeline is placed in service or; ***CORROSION CONTROL PLAN EXTERNAL COATED PIPELINES***	X			
229.		2) Is a segment that is relocated, replaced, or substantially altered?	X			

SUBPART H - CORROSION CONTROL PROCEDURES 195.402(a)			S	U	N/A	N/C
230.	Coating Materials; Coating material for external corrosion control must: a. Be designed to mitigate corrosion of the buried or submerged pipeline; b. Have sufficient adhesion to the metal surface to prevent under film migration of moisture; c. Be sufficiently ductile to resist cracking; d. Have enough strength to resist damage due to handling and soil stress; e. Support any supplemental cathodic protection; and f. If the coating is an insulating type, have low moisture absorption and provide high electrical resistance. .559***CORROSION CONTROL PLAN PROTECTIVE COATING**	X				
231.	All external pipe coatings required under 195.557 must be inspected just prior to lowering the pipe in the ditch or submerging the pipe. .561(a) ***CORROSION CONTROL PLAN EXTERNAL COATED PIPES***	X				
232.	All coating damage discovered must be repaired. .561(b) ***CORROSION CONTROL PLAN PROTECTIVE COATING***	X				
233.	Is cathodic protection applied to pipelines that have been subjected to the conditions listed in 195.557(a) within one (1) year? .563(b) ***CORROSION CONTROL PLAN CP***	X				
	Each buried or submerged pipeline converted under 195.5 must have cathodic protection if the pipeline-					
234.	1) Has cathodic protection that substantially meets 195.571 before the pipeline is placed in service, or			X		
235.	2) Is a segment that is relocated, replaced, or substantially altered?			X		
236.	c. All other buried or submerged pipelines that have an effective external coating must have cathodic protection.			X		
237.	d. Bare pipelines, breakout tank areas, and buried pumping station piping must have cathodic protection in places where previous editions of this part required cathodic protection as a result of electrical inspections.			X		
238.	e. Unprotected pipe must have cathodic protection if required by 195.573(b) .			X		
239.	Test leads installation and maintenance. .567(b)(e) ***CORROSION CONTROL PLAN TEST LEADS***	X				
240.	For placement of test stations at casing? WAC 480-75-340***CORROSION CONTROL PLAN TEST LEADS***	X				
241.	Examination of Exposed Portions of Buried Pipelines. .569***CORROSION CONTROL PLAN EXAMINATION OF BURIED PIPE***	X				
242.	Examination of pipe prior to backfilling. WAC 480-75-520***CORROSION CONTROL PLAN EXAMINATION OF BURIED PIPE***	X				
243.	Cathodic protection must comply with one or more of the applicable criteria and other considerations for cathodic protection contained in paragraphs 6.2 and 6.3 of NACE Standard RP0169-2007 (incorporated by reference). Amdt 195-94, 75 FR 48593, Pub. 8/11/10 eff. 10/01/10. .571***CORROSION CONTROL PLAN CP CRITERIA***	X				
244.	Pipe to soil monitoring (annually / 15months). .573(a) ***CORROSION CONTROL PLAN CP MONITORING***	X				
245.	(1) Separately protected short sections of bare ineffectively coated pipelines (every 3 years not to exceed 39 months).			X		
246.	(2) Identify not more than 2 years after cathodic protection is installed, the circumstances in which a close-interval survey or comparable technology is practicable and necessary to accomplish the objectives of paragraph 10.1.1.3 of NACE SP 0169-2007 . Amdt 195-94, 75 FR 48593 Pub. 8/11/10 eff. 10/01/10. ***CORROSION CONTROL PLAN CP MONITORING***	X				
	b. Unprotected buried or submerged pipe must be evaluated and cathodically protected in areas in which active corrosion is found as follows;					
247.	1) Determine areas of active corrosion by electrical survey (closely spaced pipe-to-soil survey), or where electrical survey is impractical, by other means that include review of analysis of leak repair and inspection records, corrosion monitoring records, exposed pipe inspection records, and the pipe environment			X		
248.	2) Before 12/29/2003 - at least once every 5 years not to exceed 63 months. Beginning 12/29/2003 - at least once every 3 years not to exceed 39 months.			X		

SUBPART H - CORROSION CONTROL PROCEDURES 195.402(a)			S	U	N/A	N/C
249.		c. Rectifiers, Reverse Current Switches, Diodes, Interference Bonds whose failure would jeopardize structural protection - at least 6 times each year, intervals not to exceed 2-1/2mos. ***CORROSION CONTROL PLAN CP MONITORING***	X			
250.		d. Inspect each cathodic protection system used to control corrosion on the bottom of an aboveground breakout tank to ensure that operation and maintenance of the system are in accordance with API Recommended Practice 651. (Not required if it is noted in the corrosion control procedures why compliance with all or certain operation and maintenance provisions of API Recommended Practice 651 is not necessary for the safety of the tank.) ***O&M APPENDIX 1-11***	X			
251.		e. Any deficiencies identified in corrosion control must be corrected as required by 195.401(b). ***CORROSION CONTROL PLAN REMEDIAL MEASURES FOR CORRODED PIPE***	X			
252.		Remediation of corrosion system deficiencies initiated within 90 days of discovery WAC 480-75-510 ***CORROSION CONTROL PLAN REMEDIAL MEASURES FOR CORRODED PIPE***	X			
253.		Are there adequate provisions for electrical isolations? .575 ***CORROSION CONTROL PLAN ELECTRICAL ISOLATION***	X			
254.		a. For pipelines exposed to stray currents, is there a program to minimize the detrimental effects. b. Design & install CP systems to minimize effects on adjacent metallic structures. .577 ***CORROSION CONTROL PLAN INTERFERENCE CURRENTS***	X			
255.		a. For pipelines that transport any hazardous liquid or carbon dioxide that would corrode the pipe, are corrosive effects investigated and adequate steps taken.			X	
256.		b. Internal Corrosion - Inhibitors - do procedures show that they are to be used in conjunction with coupons or other monitoring equipment to determine the effectiveness of the inhibitors in mitigating internal corrosion. .579			X	
257.		Coupons or other monitoring equipment must be examined at least 2 times each year, not to exceed 7-1/2 months.			X	
258.		c. Whenever pipe is removed from a pipeline, the internal surface of the pipe must be inspected for evidence of corrosion as well as the adjacent pipe. ***CORROSION CONTROL PLAN INTERNAL CORROSION CONTROL/ATMOSPHERIC CORROSION CONTROL***	X			
259.		Are pipelines protected against Atmospheric Corrosion using required coating material? (See exception to this statement). .581(a) ***CORROSION CONTROL PLAN ATMOSPHERIC CORROSION CONTROL***	X			
		Atmospheric corrosion monitoring - .583 ONSHORE - At least once every 3 years but at intervals not exceeding 39 months. OFFSHORE - At least once each year, but at intervals not exceeding 15 months.				
260.		(b) Inspect pipe at soil-to-air interfaces, under thermal insulation, under disbonded coatings, at pipe supports, in splash zones, at deck penetrations, and in spans over water. ***CORROSION CONTROL PLAN ATMOSPHERIC CORROSION CONTROL MONITORING***	X			
261.		(c) If atmospheric corrosion is found during an inspection, procedures for protection against the corrosion as per §195.581. ***CORROSION CONTROL PLAN ATMOSPHERIC CORROSION CONTROL MONITORING***	X			
262.		Are procedures in place and are they followed to either reduce the MOP, or repair/replace pipe if general corrosion has reduced the wall thickness? .585(a) ***CORROSION CONTROL PLAN REMEDIAL MEASURES FOR CORRODED PIPE***	X			
263.		Are procedures in place and are they followed to either reduce the MOP, or repair/replace if localized corrosion has reduced the wall thickness? .585(b) ***CORROSION CONTROL PLAN REMEDIAL MEASURES FOR CORRODED PIPE***	X			
264.		Are applicable methods used in determining the strength of corroded pipe (ASME B-31G, RSTRENG)? .587 ***CORROSION CONTROL PLAN REMEDIAL MEASURES FOR CORRODED PIPE***	X			
265.		Corrosion Control Records Retention (Some are required for 5 yrs) (Note - §§195.569, 195.573(a & b), and 195.579(b)(3) & (c) for the life of the pipeline). .589 ***CORROSION CONTROL PLAN CORROSION RECORDS***	X			

PART 199 – DRUG and ALCOHOL TESTING REGULATIONS and PROCEDURES		S	U	N/A	N/C
Subparts A - C	Drug & Alcohol Testing & Alcohol Misuse Prevention Program – Use PHMSA Form # 13, PHMSA Drug and Alcohol Program Check.				

Comments: 234-238, 247-248. Targa Sound Terminal, LLC. is all coated and cathodically protected. 245. Targa Sound Terminal, LLC. does not distribute. 255. Targa Sound Terminal, LLC. does not transport HVLs. 256. Targa Sound Terminal, LLC. does not use inhibitors, see corrosion control plan internal corrosion control. 257. Targa Sound Terminal, LLC. does not have coupons, see corrosion control plan internal corrosion control.

Recent PHMSA Advisory Bulletins (Last 2 years)

Leave this list with the operator.

<u>Number</u>	<u>Date</u>	<u>Subject</u>
ADB-2013-07	July 12, 13	Potential for Damage to Pipeline Facilities Caused by Flooding
ADB-12-10	Dec 5, 12	Using Meaningful Metrics in Conducting Integrity Management Program Evaluations
ADB-12-09	Oct 11, 12	Communication During Emergency Situations
ADB-12-08	Jul 31, 12	Inspection and Protection of Pipeline Facilities After Railway Accidents
ADB -12-06	May 7, 12	Verification of Records Establishing MAOP and MOP.
ADB-12-04	Mar 21, 12	Implementation of the National Registry of Pipeline and Liquefied Natural Gas Operators
ADB -12-03	Mar 6, 12	Notice to Operators of Driscopipe 8000 High Density Polyethylene Pipe of the Potential for Material Degradation

For more PHMSA Advisory Bulletins, go to <http://phmsa.dot.gov/pipeline/regs/advisory-bulletin>